

RYTEC

HIGH PERFORMANCE DOORS

SPIRAL[®] VP

LOWER SPEED, LOWER CYCLE RIGID DOOR

SPIRAL[®] VP

Architectural Design, Quality Construction and Unprecedented Value

Featuring the stylish design and structural integrity of the Spiral[®] high-performance door series, the Spiral VP offers a new combination of quality, value and performance in a lower speed, lower cycle design for light to moderate traffic.

Now, auto dealerships and other commercial settings can maintain a consistent aesthetic look - from front to back - without sacrificing high performance. The Spiral VP's small footprint allows the door to be installed almost anywhere a conventional overhead door fits - without visible attachment hardware. With sleek styling, quiet functioning and a compact profile, a consistent 360-degree customer experience is now a reality.

Spiral VP performance is guaranteed with a **5-year limited warranty**.



Spiral door shown

Unparalleled Performance

- High performance operation for lower speed/cycle settings
- Day in, day out reliability

Stylish Aesthetics

- Architecturally designed to complement the high-speed Spiral line of doors
- Crisp lines provide a stylish look ideal for new and existing auto dealerships and other commercial applications

Proven Durability

- Constructed with heavy-duty, high quality components

Solid Security

- Minimum 1 3/16-inch thick double walled aluminum slats
- Integral rubber weatherseal
- Continuous heavy-duty hinge system


Assured Operation

- Unmatched 20-year warranty on high-cycle components including rollers, hinges and door tracks
- Door components are the same as used on Spiral doors with millions of operating cycles

QUALITY. PERFORMANCE. RELIABILITY.

RYTECDOORS.COM

RYTEC® SPIRAL® VP DIRECT DRIVE DOOR



Size/Dimensions

- Up to 14'W x 14'H
- Multiple door configurations based on lift requirements

Travel Speed

- Opens at 12 inches per second

Operation

- Quiet, low maintenance operation
- Direct drive motor connects directly to drive shaft
- No spring or cables
- Rated for 75 cycles per day
- Compact AC drive motor with variable speeds allows for soft acceleration and deceleration
- System 4® controller housed in a NEMA 4X rated enclosure



Construction

- 'Rytec silver' powder coated finish for increased durability
- Heavy-duty extruded aluminum door hinges
- Polyurethane rollers with sealed roller bearings
- No visible mounting hardware



Powder coated side column cover



Rollers with sealed roller bearings

Warranty

- 20-year extended warranty on rollers, hinges and door track
- Five-year limited warranty on motor/mechanical components
- Two-year limited warranty on electrical components

Door Panel Configuration

- Insulated door panel
- Vision slats
- Ventilated slats
- Integrated weatherseal

Lift Configuration

- Standard lift
- Vertical lift
- High lift

Safety is Standard

- Advanced³ Light Curtain Safety System

Options

- Chain hoist operator
- Powder coated finish available in RAL classic colors or custom match

RYTEC® SPIRAL® VP BALANCED DOOR



Size/Dimensions

- Up to 14'W x 14'H
- Multiple door configurations based on lift requirements

Travel Speed

- Opens at 8 inches per second

Operation

- Torsion spring balancing system assists the motor in opening
- Aircraft quality cable lift method
- Standard overhead door operator
- Rated for 50 cycles per day



Construction

- 'Rytec silver' powder coated finish for increased durability
- Heavy-duty extruded aluminum door hinges
- Polyurethane rollers with sealed roller bearings
- No visible mounting hardware



Low-profile side track

Warranty

- 20-year extended warranty on rollers, hinges & door track
- Five-year limited warranty on motor/mechanical components
- Two-year limited warranty on electrical components

Door Panel Configuration

- Insulated door panel
- Vision slats
- Ventilated slats
- Integrated weatherseal

Lift Configuration

- Standard lift
- Vertical lift
- High lift

Safety is Standard

- Thru-beam photo eye
- Note: Not intended for automatic closing applications**

Options

- Heavy duty operator
- Chain fall
- Powder coated finish available in RAL classic colors or custom match
- Extended-life springs

Standard maximum sizes shown; larger sizes may be available upon request.

American Owned, American Made



◀ Watch All Rytec Testimonials

Specifications subject to change
© 2020 Rytec Corporation LIT020520

RytecDoors.com
888-GO-RYTEC

info@rytecdoors.com
P: 262.677.9046 F: 262.677.2058
One Cedar Parkway, PO Box 403
Jackson, WI 53037-0403

